



CROSS MATCH

L SCAN[®] 100

Compact Quick ID Scanner

There are applications in the biometrics identification field where complementary to the common complete “10-print-forms” (all 10 rolled and 4 flat control prints) the use of single flat fingerprints is required.

Visa application checking (consulates), border control (immigration), inmate handling (prison) and background checks (job applicants) are examples for quick identity checks.

The new L SCAN 100 scanner is the robust and cost efficient solution for that task. Operation is very easy and

intuitive, just place the finger on the capture platen and with a click of a button the finger is scanned. Its salient features include the live image display during the capture process, compact form, modern standard USB 2.0 PC interface, no moving parts, and solid reliability in daily use.

With its stylish outer appearance this device fits nicely into the application environment of offices and counters. Its plastic housing is stylish yet robust and lightweight. In addition it can instantly be fixed on a desk with the optional Quick Snap’n Work™ holder.

CROSS MATCH L SCAN 100

L SCAN 100 Benefits

- Capturing of live single flat fingerprints
- High scanning resolution 500 ppi, compliant with international AFIS standards
- Standard USB 2.0 interface for easiest connectivity and system integration
- Windows 2000 & XP software
- Rugged design, coating-free capture platen and optional Quick Snap'n Work™ holder

Main Features

Product components: Scanner block with USB interface cable, driver software

Computer requirements: Minimum: Pentium-class PC with Microsoft Windows 2000 SP4 or XP SP2 operating system (min. P4/2 GHz CPU, 256 MB, USB 2.0)

Scanner Functions

Scanned finger types: Single flat finger

Fingerprint capture format: 1.24" x 1.24" (31.5 x 31.5 mm)

Scanner control elements: None at the device, control and image display is done via the PC

About Cross Match Technologies, Inc.

Since its founding in 1996, Cross Match Technologies, Inc. has been at the forefront of the development and deployment of cost-effective biometric security solutions for law enforcement, federal, aviation, commercial and international organizations. Headquartered in Palm Beach Gardens, Florida, and offering the broadest product lines in the industry, Cross Match is recognized for setting new standards in fingerprint and other biometric technologies through its more than 150 existing or pending patents and related intellectual properties. Additional information on Cross Match is available at www.crossmatch.com.

Scanner power consumption: DC 5 Volts / 500 mA max. = 2.5 VA max.

Scanner power converter: No internal or external converter module required, scanner is powered via the USB 2.0 interface - therefore, the PC or a USB 2.0 hub with built-in power output provides the supply current to the scanner device

Scanner interface: USB 2.0 interface with USB connector type B

Scanner interface cable: Standard USB 2.0 compliant cable, max. length 6.2 feet (1.9 m)

Fingerprint capturing: With "live" display on PC via the capture function of the driver software

Scanner resolution: 500 pixels-per-inch (ppi) = 19.7 points -per-millimeter

Scanner dynamic range: 8 bit, max. 256 gray scales

Scanner image quality: Designed to meet the resolution requirements of the Image Quality Specification (IQS) of the FBI's Electronic Fingerprint Transmission Specification (EFTS)

Scanner output image size: 600 x 600 pixels (H x V)

Scanner Dimensions

Scanner size: (H x W x D)
3.2" x 3.3" x 6.5" (81 x 86 x 165 mm)

Scanner weight: 1.3 lbs. (520 g)

Operation and Environmental Conditions

Operating environment: Indoor (Building, Container, Car), on table-top or kiosk integrated

Interface cable protection: Cable is clamped at the scanner side and protected against access

Scanner mounting on desk: Via optional desk mount kit with Quick Snap'n Work mechanic

Operating conditions: +50...+103°F (+10...+40°C), 10...80% relative humidity, non condensing, no direct sunlight exposure

Maintenance: Daily maintenance - keep scanner clean (especially capture platen), Preventative maintenance - annual function check (via the application software, no other tools required), consumables: glass cleaner

Standards

Target reliability: MTBF 40,000 hrs., MCBF 100,000 captursings, MTTR 2 weeks (under normal operating conditions)

**CROSS
MATCH**
Technologies

US Corporate Office:
3950 RCA Boulevard
Suite 5001
Palm Beach Gardens, FL 33410
Toll Free: 866-725-3926
Phone: 561-622-1650
Fax: 561-622-9938
sales@crossmatch.com
www.crossmatch.com

European Office:
Unstrutweg 4
07743 Jena
Germany
T: +49 (0)3641 4297-0
F: +49 (0)3641 4297-14